



WetSUIT Prime Mate Water Based Primer 17-PMW

Neptune Prime Mate a high tack acrylic water based primer for use as an adhesion promoter for the WetSUIT System.

Basic Uses

Provides excellent adhesion to all roofing membranes, metal, dry concrete and dry masonry.

Technical Data

Dry Time (tack free) : 20-60 minutes

Specific Gravity: 1.03

Flash Point: n/a

Shelf Life: 6 months

Solids by Weight: 59%

Surface Preparation

All surfaces must be cleaned by brooming, vacuuming or high pressure clean dry air so that all dirt, dust, loose concrete, or other contaminants that may adversely affect the adhesion of the membrane are removed. Thinning the primer is not recommended.

Application

Prime Mate can be applied with medium nap roller or brush. Primed surface shall be free of runs, puddles, or excessive primer as this could call blistering. Brush or roll out all primer puddles or drips immediately. Prime only as much area as can be covered in half a day's work. Re-prime areas not covered in a half day's work with a light coat of Prime Mate.

Tack free is approximately 20 to 60 minutes. The opened containers, when not in use, should have the lids replaced so as to lessen the evaporation.

Please wear gloves and safety glasses when handling Prime Mate and be sure work area is well ventilated. Carefully clean up spills with warm soapy water.

Coverage

Apply at 175 to 225 square feet per gallon, depending upon porosity of the substrate. Thinning is not recommended.

Technical Services

Technical advice, for use of material in specific applications and end use requirements, is available from the manufacturer. Material Safety Data Sheet (MSDS) should be consulted for further information. This product is for industrial and professional use only.

Packaging

5 gallon pails (18.9 liters) - 46 pounds

Limitations

Apply at temperatures over 40°F (10°C)

Recommended Storage

Protect from freezing. Recommended storage temperature is 60°F to 80°F (15°C to 25°C)

Warranty

This product is manufactured of good materials and by competent workmen. Seller's and manufacturer's only obligations shall be to replace such quantity of product proved to be defective. Neither seller nor manufacturer shall be liable for injury, loss or damage, direct or consequential, arising from the use or the inability to use the product. Before using, user shall determine the suitability of the product for his/her intended use; and user assumes all risk and liability.



Toll Free: 1.800.967.7659 Phone: +1 (702) 410-5500 Fax: +1 (702) 410-5889
Email: info@neptunecoatings.com Web: neptunecoatings.com
4260 Wagon Trail Avenue, Las Vegas NV 89118 USA

*Our products are guaranteed to meet established quality control standards and product specification at time of shipment. Information contained in our technical data is based on laboratory and field testing, but is subject to change without prior notice. No guarantees of accuracy are given or implied, nor does Neptune assume any responsibility for coverage, performance or injuries resulting from storage, handling or use of our products. Neither seller nor manufacturer has any knowledge or concerning the purchaser's use. The only obligation of either seller or manufacturer shall be to replace any quantity of this product, which is proved to be defective. Any claim of defective product must be received in writing within 1 year from date of shipment.